

CLIPPEDIMAGE= JP401061730A

PAT-NO: JP401061730A

DOCUMENT-IDENTIFIER: JP 01061730 A

TITLE: BACK LIGHT SYSTEM LIQUID CRYSTAL DISPLAY DEVICE

PUBN-DATE: March 8, 1989

INVENTOR-INFORMATION:

NAME

NOZAKI, YOSHITAKA

AOKI, ISAMU

ENDO, HIDESUKE

OGAWA, HIROSHI

TORIYAMA, YOSHIO

ASSIGNEE-INFORMATION:

NAME

HITACHI LTD

HITACHI DEVICE ENG CO LTD

COUNTRY

N/A

N/A

APPL-NO: JP62217875

APPL-DATE: September 2, 1987

INT-CL (IPC): G02F001/133;G02F001/133 ;G09F009/00

US-CL-CURRENT: 359/512,362/84

ABSTRACT:

PURPOSE: To maintain the uniform brightness distribution of back light over a long period of time so that easy visibility is obtd. by disposing a glass plate to a diffusion plate on the side near the back light source.

CONSTITUTION: A cold cathode tube 6 which is the back light source is adapted to be provided in a plastic frame 5. The back light source part is constituted of the cold cathode tube 6, a reflection plate 7, a diffusion plate 8, and a

glass plate 9. The glass plate 9 has high strength and thermal deformation temp. and is not deformed even if the diffusion plate 8 is exposed to the heat of the light source for a long period of time. The diffusion plate 8, therefore, maintains always the specified relative position with the cold cathode tube 6 and the reflection plate 7 so that the specified face luminance distribution is obtd. on the diffusion plate 8 to irradiate a liquid crystal display element 1 from the rear face.

COPYRIGHT: (C)1989, JPO&Japio